

Cleaning and Care

Brecoplan/Brecoton



Introduction

A dirty floor does not give a good impression of a company. More importantly, it can be hazardous to both people and machinery.

This is why well-managed businesses pay great attention to cleaning and maintaining their premises. And it is also where our **Latanol** range of products gives you just the assistance you need, for the following applications:

- Initial cleaning
- Initial care treatment
- Ongoing wet maintenance cleaning

Product Data

Initial cleaning

Once the construction phase has been fully completed, the floor should be subjected to initial, thorough cleaning.

For this purpose, we recommend **Latanol-Fix Super**, the cleaning concentrate that we have developed especially for our industrial flooring.

Characteristics:

- Highly effective cleaner
- Solvent-free
- Non-corrosive
- Contains no acidly chemicals
- Suitable for use in food areas

Upon request, we can perform this service directly following the construction phase.

Should you wish to perform the initial cleaning yourself, you can order **Latanol-Fix Super** directly from us.

Initial care treatment

To provide a foundation for subsequent wet cleaning, we recommend performing an initial care treatment after the initial cleaning. It makes maintenance cleaning easier.

Initial care treatment is performed with our care product **Protectonol**.

Characteristics:

- Slightly dirt repellent effect
- Slight silk matt sheen

Upon request, we can also perform this service directly following the construction phase.

Naturally, if you prefer, you can also perform the initial care treatment yourself. Just order **Protectonol**.

Ongoing maintenance cleaning (wet)

Under normal conditions, it is also necessary to subject the floor to **wet cleaning**. If soiling is heavy, daily wet cleaning may even be necessary under certain circumstances. For this purpose, we recommend our cleaning concentrate, **Latanol-Fix Super**:

Characteristics:

- Great cleaning effect
- Solvent-free
- Non-corrosive
- Contains no caustic chemicals
- Suitable for use in food areas
- Suitable for use in cleaning machines

Cleaning and Care

Brecoplan/Brecofon

Preserve you floor. Systematically.

Initial cleaning with *Latanol-Fix Super*

Depending on the level of soiling, apply **Latanol-Fix Super** either with a machine or mop and leave to soak for 5 – 30 minutes, scrub, suck up, and rinse with clean water. For heavily soiled floors, apply cleaning solution, leave to soak for 15 – 60 minutes, scrub with a machine, suck up, and rinse with clean water.

Consumption

Light to moderate soiling:
mix a 5 – 10 % solution with water.
Heavy soiling:
mix with water in a ratio of 1:1

Ingredients

5 – 15 % non-ionic tensides, preserving agent, citrate, perfume.

Packaging unit

10 kg canister

Initial care treatment with *Protectonol*

Protectonol is diluted with water in ratio of 1:8 to 1:10 and applied in a thin layer to the freshly cleaned, surface-dry floor with a moist floor cloth, in a single application.

Consumption:

Approx. 0.005 kg/m² **Protectonol** concentration = 0.15 kg/m² ready mixture

Ingredients:

Thermoplastic acrylic resins based on methyl methacrylate

Packaging unit

20 kg canister

Ongoing maintenance cleaning with *Latanol-Fix Super (wet)*

Depending on the level of soiling, apply **Latanol-Fix Super** either with a machine or mop and leave to soak for 5 – 30 minutes, scrub, suck up, and rinse with clean water. For heavily soiled floors, apply cleaning solution, leave to soak for 15 – 60 minutes, scrub with a machine, suck up, and rinse with clean water.

Consumption

Light to moderate soiling:
mix a 5 – 10 % solution with water.
Heavy soiling:
mix with water in a ratio of 1:1

Ingredients

5 – 15 % non-ionic tensides, preserving agent, citrate, perfume.

Packaging unit

10 kg canister



Please send orders in writing by post, by fax to +49 421 4583-134 or by e-mail to info@dft-bremen.de. We deliver within 4 – 5 days throughout Europe. Products are supplied ex works; please request terms and conditions separately.

**DFT Deutsche Flächen-Technik
Industrieboden GmbH**
Allerkai 4 · 28309 Bremen, Germany

Telephone +49 421 4583-290
Fax +49 421 4583-280

Homepage: www.dft-bremen.de
E-mail: info@dft-bremen.de

PLEASE NOTE: For advice regarding our cleaning and care products, please call us on +49 421 4583-136.

All due care has been taken in compiling this technical data about the manufacturer's products. However, all recommendations or suggestions with respect to the use of these products are given without the assumption of any liability, as the manufacturer has no influence over the conditions under which they are used. The customer is himself responsible for determining whether the products are suitable for his intended purpose and that the conditions under which they are to be used are appropriate to the respective product.